Printing date 12.02.2023 Version number 143 (replaces version 142) Revision: 30.01.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: DUR CLEANER TI 500ML*12 L39
- · CAS Number:

78-93-3

· EC number:

201-159-0

· Index number:

606-002-00-3

- · Registration number 01-2119457290-43
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Cleaning agent/ Cleaner
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Bison International

Dr.A.F.Philipsstraat 9

NL-4462 EW Goes

PO Box 160

NL-4460 AD Goes

tel. +31 88 3235700

fax. +31 88 3235800

e mail: sds@boltonadhesives.com

- · Further information obtainable from: Bison QESH
- · 1.4 Emergency telephone number:

Members of the public seeking specific information on poisons should contact:

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The substance is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

GB-EN

Printing date 12.02.2023 Version number 143 (replaces version 142) Revision: 30.01.2023

Trade name: DUR CLEANER TI 500ML*12 L39

Hazard pictograms







GHS02 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

butanone

· Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P261 Avoid breathing vapours.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with national regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

- Labelling of packages where the contents do not exceed 125 ml
- Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

butanone

· Hazard statements

H336 May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P261 Avoid breathing vapours.

P501 Dispose of contents/container in accordance with national regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

(Contd. on page 3)

- GB-EN

6120125 - DUR CLEANER TI 500ML*12 L39

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.02.2023 Version number 143 (replaces version 142) Revision: 30.01.2023

Trade name: DUR CLEANER TI 500ML*12 L39

(Contd. of page 2)

Determination of endocrine-disrupting properties

List II

SECTION 3: Composition/information on ingredients

· 3.1 Substances

· CAS No. Description

78-93-3 butanone

· Identification number(s)

EC number: 201-159-0

· Index number: 606-002-00-3

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- General information: No special measures required.
- · After inhalation:

Supply fresh air; consult doctor in case of complaints.

No special measures required.

- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

Water haze

Alcohol resistant foam

Fire-extinguishing powder

Carbon dioxide

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- **Additional information**

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

GB-EN

(Contd. on page 4)

Printing date 12.02.2023 Version number 143 (replaces version 142) Revision: 30.01.2023

Trade name: DUR CLEANER TI 500ML*12 L39

(Contd. of page 3)

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable receptacles.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

78-93-3 butanone

WEL Short-term value: 899 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm Sk, BMGV

· DNELs

78-93-3 butanone

Oral	Consumer, oral, longterm exposition	31 mg/kg bw/day
Dermal	Consumer, dermal, longterm exposition	412 mg/kg bw/day
Inhalative	Consumer, inhalation, longterm exposition	106 mg/m³

(Contd. on page 5)

Version number 143 (replaces version 142) Revision: 30.01.2023 Printing date 12.02.2023

Trade name: DUR CLEANER TI 500ML*12 L39

		(Contd. of p	age 4)
·PNECs			
78-93-3 b	outano	one	
Fresh wa	ter 5	55.8 mg/l	
Marine wa	ater 5	55.8 mg/l	
Soil	22	22.5 mg/kg	
· Ingredier	nts wit	ith biological limit values:	
78-93-3 b	outano	one	
	BMGV 70 µmol/L		
	Medium: urine		
S	amplin	ing time: post shift	
P	arame	eter: butan-2-one	

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

- Recommended filter device for short term use: Filter A
- Hand protection

Solvent resistant gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Recommended thickness of the material: > 0,12 mm

Butvl rubber, BR

Nitrile rubber, NBR

Recommended thickness of the material: > 0,7 mm

Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

For the mixture of chemicals mentioned below the penetration time has to be at least 120 minutes (Permeation according to EN 374 Part 3: Level 4).

Eye/face protection



Tightly sealed goggles

(Contd. on page 6)

Version number 143 (replaces version 142) Revision: 30.01.2023 Printing date 12.02.2023

Trade name: DUR CLEANER TI 500ML*12 L39

(Contd. of page 5)

Goggles recommended during refilling

· Body protection: Solvent resistant protective clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Fluid Colourless · Colour: · Odour: Like ketone · Odour threshold: Not determined. -86.3 °C

Melting point/freezing point:

· Boiling point or initial boiling point and

boiling range 79-80.5 °C · Flammability Highly flammable.

· Lower and upper explosion limit

· Lower: 1.8 Vol % · Upper: 11.5 Vol % · Flash point: -9 °C 514 °C · Ignition temperature:

Decomposition temperature: Not determined. · pH Not determined.

· Viscosity:

· Kinematic viscosity Not determined. · Dynamic at 20 °C: 0.4 mPas

· Solubility

· water at 20 °C: 290 g/l

Partition coefficient n-octanol/water (log

Not determined. value) Vapour pressure at 20 °C: 105 hPa

Density and/or relative density

Density at 20 °C: 0.804-0.807 g/cm³ Not determined. · Relative density · Vapour density Not determined.

· 9.2 Other information All relevant physical data were determined for the

mixture. All non-determined data are not measurable or not relevant for the

characterization of the mixture.

· Appearance:

· Form: Fluid

· Important information on protection of health and environment, and on safety.

Auto-ignition temperature: Not determined.

· Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Organic solvents: 100.0 % 0.0 % · Solids content: 72.11 g/mol Molecular weight

(Contd. on page 7)

Printing date 12.02.2023 Version number 143 (replaces version 142) Revision: 30.01.2023

Trade name: DUR CLEANER TI 500ML*12 L39

(Contd. of page 6)

•	Change	ın	condi	tion
	_			

• Evaporation rate Not determined.

Information with regard to physical hazard classes

Explosives
Flammable gases
Aerosols
Oxidising gases
Gases under pressure

Void
Void
Void

• Flammable liquids Highly flammable liquid and vapour.

Flammable solids
 Self-reactive substances and mixtures
 Pyrophoric liquids
 Pyrophoric solids
 Self-heating substances and mixtures
 Substances and mixtures, which emit flammable gases in contact with water

Substances and mixtures, which emit flammable gases in contact with water
 Oxidising liquids
 Oxidising solids
 Organic peroxides
 Corrosive to metals
 Desensitised explosives

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: Danger of forming toxic pyrolysis products.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

78-93-3 butanone

Oral LD50 3300 mg/kg (rat)
Dermal LD50 5000 mg/kg (rabbit)

- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation

Causes serious eye irritation.

· **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

(Contd. on page 8)

GR EN

Printing date 12.02.2023 Version number 143 (replaces version 142) Revision: 30.01.2023

Trade name: DUR CLEANER TI 500ML*12 L39

(Contd. of page 7)

Germ cell mutagenicity

Not applicable.

Based on available data, the classification criteria are not met.

- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · **Aspiration hazard** Based on available data, the classification criteria are not met.
- Additional toxicological information:
- · Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- Sensitisation Not applicable.
- Repeated dose toxicity Not applicable.
- 11.2 Information on other hazards
- Endocrine disrupting properties

List II

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB**: Not applicable.
- 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Assessment by list): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

(Contd. on page 9)

GB-EN

Printing date 12.02.2023 Version number 143 (replaces version 142) Revision: 30.01.2023

Trade name: DUR CLEANER TI 500ML*12 L39

(Contd. of page 8)

- · Uncleaned packaging:
- Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

14.1 UN number or ID number	
ADR/ADN, IMDG, IATA	UN1193
· 14.2 UN proper shipping name · ADR/ADN	1193 ETHYL METHYL KETONE (METHY ETHYL KETONE)
· IMDG, IATA	ETHYL METHYL KETONE (METHYL ETH) KETONE)
14.3 Transport hazard class(es)	
ADR/ADN	
Class	3 (F1) Flammable liquids.
· Label · IMDG, IATA	3
Class	3 Flammable liquids.
Label	3
· 14.4 Packing group · ADR/ADN, IMDG, IATA	II
· 14.5 Environmental hazards: · Marine pollutant:	No
	Warning: Flammable liquids.
· Hazard identification number (Kemler code): · EMS Number:	33 F-E,S-D
Stowage Category	Р-E,S-D В
14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
Transport/Additional information:	_
Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
	•

- GB-EN

Printing date 12.02.2023 Version number 143 (replaces version 142) Revision: 30.01.2023

Trade name: DUR CLEANER TI 500ML*12 L39

(Contd. of page
1L
Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 50
ml
2
D/E
1L
Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 50
ml
Under certain conditions substances in Class
(flammable liquids) can be classified in
packinggroup III.
See IMDG, Part 2, Chapter 2.3, Paragraph 2.3.2.2
UN 1193 ETHYL METHYL KETONE (METHY
ETHYL KETONE), 3, II

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I Substance is not listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

Substance is not listed.

- · REGULATION (EU) 2019/1148
- Regulation (EC) No 273/2004 on drug precursors

3

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

3

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

GB-EN

(Contd. on page 11)

6120125 - DUR CLEANER TI 500ML*12 L39

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.02.2023 Version number 143 (replaces version 142) Revision: 30.01.2023

Trade name: DUR CLEANER TI 500ML*12 L39

(Contd. of page 10)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· Department issuing SDS: Bison QESH

· Contact: Reach coordinator

Date of previous version: 28.06.2022
 Version number of previous version: 142

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning

the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (ÚK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

* Data compared to the previous version altered.

GB-EN